



SHORELINE SURVEYS LTD
 Hydrographic — Geophysical — Topographic

Moreford Hall, Moreton, Dorchester, Dorset DT2 8BA
 Telephone: +44 1305 848821 or +44 7950 038317
 email@shorelinesurveys.com — www.shorelinesurveys.com

TITLE:
 Bathymetric & side scan sonar survey within the Isles of Scilly: St Mary's Harbour

CLIENT:
 Duchy of Cornwall — Harbour Authority

PROJECT:
 2022 check survey

Project No: J2042 Scale: 1:11000 Date: 30.05.22 Surveyed by: EF
 Drawing No: 02/04 Drawn by: TC, PL Checked by: EF

NOTES/REVISIONS:
 Contours are only indicative of bed topography and should be treated as such. These data is approximate and should be treated as such.
 33 Mooring buoy — positioned at request of Harbour Master — i.e. not of harbour. See supplied table for more data.

DO NOT SCALE
 COPYRIGHT

MULTIBEAM SURVEY
 Coordinated in OSTN15.
 Depths below Chart Datum (CD) in metres.
 CD taken as 2.91 metres below Ordnance Datum Newlyn (ODN).
 RTK GNSS, tidal and IMU data post-processed using PostPAC MMS.
 Soundings sorted at 4.0 metre intervals using IHO rounding rules.
 Contours at 0.25 metre intervals.
 Survey coverage is not 100%.
 Bed mounted obstructions are not certainly detected.

SIDE SCAN SONAR SURVEY
 Side scan data used to validate rocks, shallow features and obstructions which are present in the multibeam data.
 Sub-seabed obstructions are not detected.
 Side scan sonar survey line spacing: Typically 30 metres.
 Side scan sonar operated at 325kHz, typically 50 metre range.
 Side scan sonar survey limit (seaward of this line)

⊙ Areas of dense vegetation and/or rocks. Soundings in these areas have lower confidence values.

